

POLY PRIMER ALIPHATIC

Page: 1

Compilation date: 05/06/2015

Revision date: 01/04/2021

Revision No: 7

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: POLY PRIMER ALIPHATIC

REACH registered number(s): EXEMPT UNDER REACH IN ACCORDANCE WITH ARTICLE II, SECTION 9

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Primer for Polyurethane binder

1.3. Details of the supplier of the safety data sheet

Company name: Polytech Liquid Polymers Limited

Nab Works
Pott Shrigley
Macclesfield
Cheshire
SK10 5SD

United Kingdom

Tel: +44 (0) 1625 575737 **Fax:** +44 (0) 1625 560180

Email: bob.hancock@MRi-Polytech.com

1.4. Emergency telephone number

Emergency tel: +44 (0) 1625 575737

(office hours only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Acute Tox. 4: H302+H332; Asp. Tox. 1: H304; Skin Irrit. 2: H315; Skin Sens. 1: H317;

STOT SE 3: H335; -: EUH208

Most important adverse effects: Contains hexamethylene-di-isocyanate. May produce an allergic reaction. Harmful if

swallowed or if inhaled May be fatal if swallowed and enters airways. Causes skin irritation. May cause an allergic skin reaction. May cause respiratory irritation.

2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains hexamethylene-di-isocyanate. May produce an allergic reaction.

H302+H332: Harmful if swallowed or if inhaled

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

POLY PRIMER ALIPHATIC

Page: 2

H317: May cause an allergic skin reaction.

H335: May cause respiratory irritation.

Hazard pictograms: GHS07: Exclamation mark

GHS08: Health hazard





Signal words: Danger

Precautionary statements: P260: Do not breathe dust/fumes/gas/mist/vapours/spray.

P280: Wear protective gloves/protective clothing/eye protection/face protection.
P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor.
P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for

breathing.

P331: Do NOT induce vomiting.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-199-0	64742-95-6	-	Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; Aquatic Chronic 2: H411	10-30%

ALIPHATIC POLYISOCYANATE OLIGOMER - REACH registered number(s): 01-2119485796-17-XXXX

500-060-2	28182-81-2	-	Acute Tox. 3: H331; Skin Sens. 1:	10-30%
			H317; STOT SE 3: H335	

ALKYL DIISOCYANATE PRODUCTS - REACH registered number(s): EXEMPT UNDER REACH IN ACCORDANCE WITH ARTICLE II, SECTION 9

Skin Irrit. 2: H315 10-30%

HEXAMETHYLENE-DI-ISOCYANATE

212-485-8	822-06-0	-	Acute Tox. 3: H331; Eye Irrit. 2: H319;	<1%
			STOT SE 3: H335; Skin Irrit. 2: H315;	
			Resp. Sens. 1: H334; Skin Sens. 1:	
			H317	

Section 4: First aid measures

POLY PRIMER ALIPHATIC

Page: 3

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still

on skin. Consult a doctor.

Eye contact: Bathe the eye with running water for 15 minutes. Consult a doctor.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water

to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so. Consult a

doctor.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. If outside do not approach from

downwind. If outside keep bystanders upwind and away from danger point. Mark out the

contaminated area with signs and prevent access to unauthorised personnel. Turn

leaking containers leak-side up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

POLY PRIMER ALIPHATIC

Page: 4

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area.

Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. The floor of the

storage room must be impermeable to prevent the escape of liquids.

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

HEXAMETHYLENE-DI-ISOCYANATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	0.02 mg/m3	0.07 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. The floor of the storage room must be

impermeable to prevent the escape of liquids.

Respiratory protection: Self-contained breathing apparatus must be available in case of emergency.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Impermeable protective clothing.

Environmental: Prevent from entering in public sewers or the immediate environment.

Section 9: Physical and chemical properties

POLY PRIMER ALIPHATIC

Page: 5

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Colourless

Odour: Characteristic odour

Evaporation rate: Slow

Solubility in water: Insoluble, reacts with water

Viscosity: Non-viscous

Kinematic viscosity: >20.5

Viscosity test method: Kinematic viscosity in 10-6 m2/s at 40°C (ISO 3104/3105)

Boiling point/range°C: >35 Flash point°C: 60 - 93

Relative density: 1.04 pH: Approx. 7

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

LOW BOILING POINT NAPHTHA - UNSPECIFIED - SOLVENT NAPHTHA (PETROLEUM), LIGHT AROM.

ORL	RAT	LD50	8400	mg/kg	

POLY PRIMER ALIPHATIC

Page: 6

HEXAMETHYLENE-DI-ISOCYANATE

IVN	MUS	LD50	5600	μg/kg
ORL	MUS	LD50	350	mg/kg
ORL	RAT	LD50	710	μl/kg

Relevant hazards for product:

Hazard	Route	Basis
Acute toxicity (ac. tox. 4)	INH ING	Hazardous: calculated
Skin corrosion/irritation	DRM	Hazardous: calculated
Respiratory/skin sensitisation	DRM	Hazardous: calculated
STOT-single exposure	INH	Hazardous: calculated
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be irritation and redness at the site of contact.

Eye contact: There may be irritation and redness. The eyes may water profusely.

Ingestion: There may be soreness and redness of the mouth and throat. Nausea and stomach

pain may occur. There may be vomiting.

Inhalation: There may be irritation of the throat with a feeling of tightness in the chest.

Delayed / immediate effects: Immediate effects can be expected after short-term exposure.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Not biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: Bioaccumulation potential.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Toxic to aquatic organisms. Toxic to soil organisms.

Section 13: Disposal considerations

POLY PRIMER ALIPHATIC

Page: 7

13.1. Waste treatment methods

Disposal operations: Either return any unused product to the supplier, or Transfer to a suitable container and

arrange for collection by specialised disposal company.

Waste code number: 08-04-10* (20-01-27*)

Disposal of packaging: Allow container residue to moisture cure to an inert polyurethane resin. Dispose of as

normal industrial waste.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

Transport class: This product does not require a classification for transport.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No

2015/830.

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: EUH208: Contains hexamethylene-di-isocyanate. May produce an allergic reaction.

H226: Flammable liquid and vapour.

H302+H332: Harmful if swallowed or if inhaled

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H319: Causes serious eye irritation.

H331: Toxic if inhaled.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.